

Information Analysis

OWL Intuition-pv widget with real time energy and cost / CO2 emissions information

Quick comparison of recent periods

Quick recent trend indicators (hover over for additional information)

Graphs have quick selection buttons:

Time Frames – show data for last 1 day, 1 week,

1 month, 3 months, 6 months

Grouped By – None (full detail), Day, Week,

Month, Year

Display – Energy consumed, Cost of energy

consumed, CO2e of energy consumed

Hover over graphs for detail

Print graph

Download:

Graph as PDF document, JPEG image, PNG image

or SVG vector image

Comma-separated values (CSV) file for use in

Excel or other spreadsheets

Push data streams for those wishing to collect and analyse own

data:

Multicast data broadcast on local network

External UDP data push

Technical

Operating frequency:

Transmitter - 433MHz

Network OWL Gateway – 433MHz and 868MHz

Operating range up to 30m

12 second refresh rate (Electricity consumption data)

Transmitter battery life > 14 months

Sensor suitable to monitor cables rated up to 71A

Storage conditions: -25 °C to +65 °C

Relative humidity: 25% to 95% non-condensing

Operating temperature: 0 °C to 40 °C

Ingress protection: IP30

Standards

IEC 61010-1:2001(2nd Edition) / EN 61010-1:2001(2nd Edition)

ETSI EN 300 220-1 V2.1.1 (2006-04) / ETSI EN 300 220-2 V2.1.2

(2007-06)

ETSI EN 301 489-1 V1.8.1 (2008-04) / ETSI EN 301 489-3 V1.4.1

(2002-08)

R&TTE - WEEE Directive, RoHS, Battery Directive

Includes

Network OWL Gateway with external antenna

Plug top power supply – 240V UK

Ethernet cable

3 channel Transmitter unit

2 x standard Sensor clamp (< 10mm cable, < 71A)

3 x AA alkaline battery

Installation /User Manual

Options

Large Sensor clamp (> 10mm cable, < 200A)



Extending the domestic system

OWL Intuition-pv is only a first step towards really significant energy and cost savings. It will make a big difference to your knowledge about electricity usage and will help you change simple things that will reduce your electricity consumption.

It is a little known fact, however, that over 80% of the energy consumed in the home is used for heating and hot water. **OWL Intuition** brings heating and hot water control into the Internet Age. The intelligent control system has numerous energy saving and ease of use features. For example, it can take the occupancy of the home into account – why waste energy and money heating your home when there is nobody in? **OWL Intuition** is designed to save energy without sacrificing comfort. For example, the energy saved by being able to delay the heating coming on when you are going to be late home – or the convenience and comfort of being able to turn the heating on before coming home early on a cold day?

Please visit our web site for further information on

OWL Intuition.

www.theowl.com/intuition



2 Save Energy Ltd

The Annexe, Field House Barn

Chineham Lane, Sherborne St John

Basingstoke, Hants RG24 9LR UK

Tel: +44 1256 383 430

www.theowl.com



ONL Intuition-pv
new generation energy monitoring



energyoptions.net.au

Informed Solutions



OWL Intuition-pv is a new **OWL** product created to compliment and monitor your Solar PV installation.

OWL Intuition-pv provides real-time access to your electricity consumption and solar generation data through your web browser, smart phone or tablet.*

OWL Intuition-pv is part of a new and expanding family of intelligent, cloud based energy monitoring and control solutions for domestic and commercial premises.

* Phone and Android apps due to launch Q2 2012.

make your home an **ONL** home



OWL Intuition-pv is a new OWL product created to compliment and monitor your Solar PV installation. **OWL Intuition-pv** provides real-time access to your electricity consumption and solar generation data through your web browser, smart phone or tablet.*

How does it work?

The **Network OWL** gateway automatically logs all of your consumption and generation data securely within the Intelligent Cloud software platform. You can then login to view your live and historic data, from any Internet connected computer, anywhere! Or if you wish, access **OWL Intuition-pv** on your smartphone using a dedicated iPhone or Android app - both available for free download. **Network OWL** gateway simply plugs into your existing broadband router and wirelessly links with the Transmitter and two Sensors.

OWL Intuition-pv is part of a new and expanding family of intelligent, cloud based energy monitoring and control solutions for domestic and commercial premises.



Features

- Energy data is automatically and continuously collected and stored within the Intelligent Cloud via a Network OWL connected to your existing broadband Internet connection
- Real time and accumulated data can be viewed via:
 - Web browsers (including iPad)
 - iPhone and Android smartphones
 - OWL energy monitors
- Clear summary information with trend indicators and “hover over” analysis
- Easy to read graphs with hover over detail values
- Print or download graphs
- Supports block tariff based on usage
- Supports Economy 7 and other common timed tariffs
- Configurable real time consumption EcoNudge™ messages
- Download CSV data file for your own analysis
- Optional data push via Multicast or UDP protocols
- Software is upgradable to provide access to future new features and services

System Design

OWL Intuition-pv allows you to monitor how much Solar PV power is being generated, the energy your home is currently consuming and hence how much power is being imported from or exported to the grid. Two separate Sensor clamps need to be fitted as shown in the Type One diagram opposite. **NOTE:** Type Two installations, where the Solar PV power is fed directly into the consumer unit, are not currently supported.

* iPhone and Android apps due to launch Q2 2012.
 Web browsers must have JavaScript enabled.
 OWL Intuition is optimised for use on Internet Explorer 9+; Safari 5+;
 Safari iOS 5+; Chrome 17+
 Existing OWL energy monitors can also receive the same wireless updates – note no additional functionality is available on these dedicated interfaces.

